

## **NA2XB(AL)2Y ( Al / XLPE / ATA / PE )**

*(Aluminium Conductor, XLPE Insulated, Aluminium Tape Armor, PE Sheathed)*

### **Standard Specification :**

SNI IEC 60502-1 : 2009

IEC 60502-1

Other specifications are available upon request

### **Rated Voltage :**

0.6/1 kV

### **Number of core :**

1 core

### **Cross Sectional Area :**

16 – 800 mm<sup>2</sup>

### **Application :**

For installation indoors, cable channels and in ground, for industry installations, switchgear, and power station, if there is a risk that low mechanical damage may occur.

### **Special Features on Request :**

- Oil Resistance
- UV Resistance
- Flame Retardant Cat. A, B, C
- Flame Retardant Non Category
- Anti Termite
- Anti Rodent
- Low Smoke Zero Halogen
- Lead Sheathed

### **Note :**

#### **Conductor Shape**

*16 sqmm supplied in non compacted circular stranded (rm) conductor shape*

*25 - 800 sqmm supplied in non compacted circular stranded (rm) or compacted circular stranded (cm) conductor shape*

#### **Standard Packing**

*16 - 300 sqmm supplied in wooden drum @ 1000 m*

*400 - 800 sqmm supplied in wooden drum on available length*

*Length Tolerance per drum ± 2%*

## **NA2XB2Y ( AI / XLPE / STA / PE )**

*(Aluminium Conductor, XLPE Insulated, Galvanized Steel Tape Armor, PE Sheathed)*

### **Standard Specification :**

SNI IEC 60502-1 : 2009

IEC 60502-1

Other specifications are available upon request

### **Rated Voltage :**

0.6/1 kV

### **Number of cores :**

2 - 5 core

### **Cross Sectional Area :**

10 – 300 mm<sup>2</sup>

### **Application :**

For installation indoors, cable channels and in ground, for industry installations, switchgear, and power station, if there is a risk that low mechanical damage may occur.

### **Special Features on Request :**

- Oil Resistance
- UV Resistance
- Flame Retardant Cat. A, B, C
- Flame Retardant Non Category
- Anti Termite
- Anti Rodent
- Low Smoke Zero Halogen
- Lead Sheathed

### **Note :**

#### **Conductor Shape**

10 - 16 sqmm supplied in non compacted circular stranded (rm) conductor shape

25 - 300 sqmm supplied in non compacted circular stranded (rm) or compacted circular stranded (cm) conductor shape

#### **Standard Packing**

10 - 120 sqmm supplied in wooden drum @ 1000 m

150 - 300 sqmm will be supplied in wooden drum on available length

Length Tolerance per drum  $\pm$  2%