

## **NA2XFGbY (Al / XLPE / SFWA / PVC)**

*(Aluminium Conductor, XLPE Insulated, Galvanized Steel Flat Wire Armor, PVC Sheathed)*

### **Standard Specification :**

SNI IEC 60502-1 : 2009

IEC 60502-1

Other specifications are available upon request

### **Rated Voltage :**

0.6/1 kV

### **Number of cores :**

2 - 5 core

### **Cross Sectional Area :**

10 – 300 mm<sup>2</sup>

### **Application :**

For installation in the ground, indoors, cable trunking and outdoors if increased mechanical protection is required or where high-pulling stresses may occur during installation or operation.

### **Special Features on Request :**

- Oil Resistance
- UV Resistance
- Flame Retardant Cat. A, B, C
- Flame Retardant Non Category
- Anti Termite
- Anti Rodent
- Low Smoke Zero Halogen
- Lead Sheathed

### **Note :**

#### **Conductor Shape**

10 - 16 sqmm supplied in non compacted circular stranded (rm) conductor shape

25 - 300 sqmm supplied in compacted circular stranded (cm) conductor shape

#### **Standard Packing**

10 - 150 sqmm supplied in wooden drum @ 1000 m

185 - 300 sqmm will be supplied in wooden drum on available length

Length Tolerance per drum  $\pm 2\%$