

## **NAYB(AL)Y (AI / PVC / ATA / PVC)**

*(Aluminium Conductor, PVC Insulated, Aluminium Tape Armor, PVC Sheathed)*

### **Standard Specification :**

SNI IEC 60502-1 : 2009

IEC 60502-1

Other specifications are available upon request

### **Rated Voltage :**

0.6/1 kV

### **Number of core :**

1 core

### **Cross Sectional Area :**

16 – 800 mm<sup>2</sup>

### **Application :**

For installation indoors, cable channels and in ground, for industry installations, switchgear, and power station, if there is a risk that low mechanical damage may occur.

### **Special Features on Request :**

- Oil Resistance
- UV Resistance
- Flame Retardant Cat. A, B, C
- Flame Retardant Non Category
- Heat Resistance
- Anti Termite
- Anti Rodent
- Low Smoke Zero Halogen
- Lead Sheathed

### **Note :**

#### **Conductor Shape**

16 sq.mm supplied in non compacted circular stranded (rm) conductor shape

25 - 800 sqmm supplied in non compacted circular stranded (rm) or compacted circular stranded (cm) conductor shape

#### **Standard Packing**

16 - 300 sqmm supplied in wooden drum @ 1000 m

400 - 800 sqmm supplied in wooden drum on available length

Length Tolerance per drum  $\pm 2\%$