

NAYC2Y (AI / PVC / CWS / PE)

(Aluminium Conductor, PVC Insulated, Copper Wire Screen, PE Sheathed)

Standard Specification :

SNI IEC 60502-1 : 2009

IEC 60502-1

Other specifications are available upon request

Rated Voltage :

0.6/1 kV

Number of cores :

1 - 5 core

Cross Sectional Area :

10 – 800 mm²

Application :

For installation in the ground, indoors, cable trunking and outdoors if subsequent mechanical damage is likely. For urban networks, household feeders and street lighting.

Special Features on Request :

- Oil Resistance
- UV Resistance
- Flame Retardant Cat. A, B, C
- Flame Retardant Non Category
- Heat Resistance
- Anti Termite
- Anti Rodent
- Low Smoke Zero Halogen
- Lead Sheathed

Note :

Conductor Shape

10 - 16 sq.mm supplied in non compacted circular stranded (rm) conductor shape

25 - 800 sqmm supplied in non compacted circular stranded (rm) or compacted circular stranded (cm) conductor shape

Standard Packing

• Single Core

10 - 240 sqmm supplied in wooden drum @ 1000 m

300 - 800 sqmm supplied in wooden drum on available length

• Multi core

10 - 95 sqmm supplied in wooden drum @ 1000 m

120 - 300 sqmm will be supplied in wooden drum on available length

Length Tolerance per drum $\pm 2\%$