

## **NAYFGbY ( AL / PVC / SFWA / PVC )**

*(Aluminium Conductor, PVC Insulated, Galvanized Steel Flat Wire Armor, PVC Sheathed)*

### **Standard Specification :**

SNI IEC 60502-1 : 2009

IEC 60502-1

Other specifications are available upon request

### **Rated Voltage :**

0.6/1 kV

### **Number of cores :**

2 - 5 core

### **Cross Sectional Area :**

10 – 300 mm<sup>2</sup>

### **Application :**

For installation in the ground, indoors, cable trunking and outdoors if increased mechanical protection is required or where high-pulling stresses may occur during installation or operation.

### **Special Features on Request :**

- Oil Resistance
- UV Resistance
- Flame Retardant Cat. A, B, C
- Flame Retardant Non Category
- Heat Resistance
- Anti Termite
- Anti Rodent
- Low Smoke Zero Halogen
- Lead Sheathed

### **Note :**

#### **Conductor Shape**

*10 - 16 sqmm supplied in non compacted circular stranded (rm) conductor shape*

*25 - 800 sqmm supplied in non compacted circular stranded (rm) or compacted circular stranded (cm) conductor shape*

#### **Standard Packing**

*10 - 95 sqmm supplied in wooden drum @ 1000 m*

*120 - 300 sqmm will be supplied in wooden drum on available length*

*Length Tolerance per drum ± 2%*