

## **N2XRGBY ( Cu / XLPE / SWA / STA / PVC )**

*(Copper Conductor, XLPE Insulated, Galvanized Steel Wire Armor, Galvanized Steel Tape, PVC Sheathed)*

### **Standard Specification :**

SNI IEC 60502-1 : 2009

IEC 60502-1

Other specifications are available upon request

### **Rated Voltage :**

0.6/1 kV

### **Number of cores :**

6 - 61 core

### **Cross Sectional Area :**

1.5 – 6 mm<sup>2</sup>

### **Application :**

As control cable for installation in the ground, indoors, cable trunking and outdoors if increased mechanical protection is required or where high-pulling stresses may occur during installation or operation.

### **Special Features on Request :**

- Tinned Coated Copper Conductor
- Fire Resistance
- Oil Resistance
- UV Resistance
- Flame Retardant Cat. A, B, C
- Flame Retardant Non Category
- Anti Termite
- Anti Rodent
- Low Smoke Zero Halogen
- Lead Sheathed

### **Note :**

#### **Conductor Shape**

Supplied in solid (re) or non compacted circular stranded (rm)

#### **Standard Packing**

6 – 40 cores supplied in wooden drum @ 1000 m

> 40 cores will be supplied in wooden drum on available length

Length Tolerance per drum  $\pm 2\%$