

N2XY (CU / XLPE / PVC) (Copper Conductor, XLPE Insulated, PVC Sheathed)

Standard Specification :

SNI IEC 60502-1 : 2009

IEC 60502-1

Other specifications are available upon request

Rated Voltage :

0.6/1 kV

Number of cores :

1 - 5 core

Cross Sectional Area :

1.5 – 800 mm²

Application :

Power cable : indoors, cable trunking, outdoors and buried in the ground, for power stations, industry and switchgear as well as for urban supply networks, if mechanical damage is unlikely.

Special Features on Request :

- Tinned Coated Copper Conductor Anti Termite
- Fire Resistance Anti Rodent
- Oil Resistance Low Smoke Zero Halogen
- UV Resistance Lead Sheathed
- Flame Retardant Cat. A, B, C Nylon Coated
- Flame Retardant Non Category

Note :

Conductor Shape

1.5 - 10 sq.mm supplied in solid (re) or non compacted circular stranded (rm)

16 sq.mm supplied in non compacted circular stranded (rm) conductor shape

25 - 800 sqmm supplied in non compacted circular stranded (rm) or compacted circular stranded (cm) conductor shape

Standard Packing

• **Single Core**

1.5 - 10 sqmm supplied in coil @ 100 m

16 - 400 sqmm supplied in wooden drum @ 1000 m

500 - 800 sqmm supplied in wooden drum on available length

• **Multi core**

1.5 - 120 sqmm supplied in wooden drum @ 1000 m

150 - 300 sqmm will be supplied in wooden drum on available length

Length Tolerance per drum $\pm 2\%$