

**NA2XSERY (Al / XLPE / CTS / PVC / SWA / PVC )**  
(Aluminium Conductor, XLPE Insulated, Copper Tape Screen, Galvanized Steel Wire Armor, PVC Sheathed)

**Standard Specification :**

SNI IEC 60502-2 : 2009

IEC 60502-2

Other specifications are available upon request

**Rated Voltage :**

3.6/6 kV up to 18/30 kV

**Number of cores :**

3 core

**Cross Sectional Area :**

25 – 300 mm<sup>2</sup>

**Application :**

For installation in the ground, indoors, cable trunking and outdoors if increased mechanical protection is required or where high-pulling stresses may occur during installation or operation.

**Special Features on Request :**

- Oil Resistance
- UV Resistance
- Flame Retardant Cat. A, B, C
- Flame Retardant Non Category
- Anti Termite
- Anti Rodent
- Low Smoke Zero Halogen
- Lead Sheathed

**Note :**

**Conductor Shape**

25 - 300 sqmm supplied in compacted circular stranded (cm) conductor shape

**Standard Packing**

25 - 50 sqmm supplied in wooden drum @ 1000 m

50 - 300 sqmm will be supplied in wooden drum on available length

Length Tolerance per drum  $\pm 2\%$