

## **N2XSEFGb2Y ( Cu / XLPE / CTS / PVC / SFWA / PE )**

*(Copper Conductor, XLPE Insulated, Copper Tape Screen, Galvanized Steel Flat Wire Armor, PE Sheathed)*

### **Standard Specification :**

SNI IEC 60502-2 : 2009

IEC 60502-2

Other specifications are available upon request

### **Rated Voltage :**

3.6/6 kV up to 18/30 kV

### **Number of cores :**

3 core

Cross Sectional Area :

25 – 300 mm<sup>2</sup>

### **Application :**

For installation in the ground, indoors, cable trunking and outdoors if increased mechanical protection is required or where high-pulling stresses may occur during installation or operation.

### **Special Features on Request :**

- Tinned Coated Copper Conductor
- Oil Resistance
- UV Resistance
- Flame Retardant Cat. A, B, C
- Flame Retardant Non Category
- Anti Termite
- Anti Rodent
- Low Smoke Zero Halogen
- Lead Sheathed

### **Note :**

#### **Conductor Shape**

25 - 300 sqmm supplied in compacted circular stranded (cm) conductor shape

#### **Standard Packing**

25 - 50 sqmm supplied in wooden drum @ 1000 m

70 - 300 sqmm will be supplied in wooden drum on available length

Length Tolerance per drum  $\pm 2\%$